



SCAFFOLD WORKER SOCKET (JAWS LOCK)







absorbing



The bolt or nut, even rounded, can fit into the newly designed socket which has a wide area of contact. The JAWS LOCK, VESSEL's unique jagged forging process, catches the rounded edges of such bolt or nut. when loosening.

Can tighten the rounded bolt or nut because of contactarea.

Shank with shock absorbing material

Torsion effect and shock absorbing material prevent the shank breakage.

5 times more durability than our conventional socket LAS20179.

Example of dedicated POP display materials.

(Please contact our sales person for more detail)

▼Shelf Wobbler W70×H170mm

▼POP Display for Hanging Strip W80×H80mm



Hanging Merchandise Strip Display W37.5×H600mm

*The design and other specifications may be subject to change without notice






Hexagonal surface contact that has never existed.


Applied to any hex bolt and nut. JAWS LOCK

No. MLS20179 Scafford Worker Socket (JAWS LOCK)



Easy fitting dodecagonal socket. Remarkably improved workability.

No. LAS20179 Scaffold Worker Socket



Inner Ctn.:5pcs, Outer Ctn.:100pcs

●Carefully read the instruction manual of the power tool before use. ●Be sure to wear protective goggles when working. •Make sure to shut off the power source when installing or replacing the bit. •Do not use if any abnormality such as cracking, chipping, wear or deformation is found.

Never allow idle rotation by attaching to a power tool. ●Do not use for objects that have electricity flowing through them. ●Do not modify.

ESSEL Co., Inc.

17-25, Fukae-Kita 2-chome, Higashinari-ku, Osaka 537-0001 JAPAN Tel:+ 81 (0) 6 6976 7778 Fax:+ 81 (0) 6 6972 9441 E-mail:export@vessel.co.jp URL: www.vessel.co.jp/english/

VESSEL EUROPE

contact@vessel-europe.com www.vessel-europe.com

VESSEL TOOLS U.S.A., INC.

2701 Plaza Del Amo #706 Torrance, CA 90503, U.S.A Tel: +1-424-427-5441

E-mail:kkimura@vessel.co.jp/ y-nakajima@vessel.co.jp URL: www.vesseltoolsusa.com

Distributed by

Inner Ctn.:5pcs, Outer Ctn.:100pcs

22010000 00