

*New*

# Wire Stripper No.3500E-6/-7

Made in Japan

Supports upto **8sq.**  
wires that are used for  
grounding cables and jointed cables.

3500E-6

# Newly supports wire diameters required

for electrical and  
telecommunication  
equipment wiring.

3500E-7

Can strip 2-pc.  
wire sheath of twisted pair cables  
at the same time.

For more information



3500E-7 : Applicable wires

	0.65	0.9	1.2	1.6	2.0	2.6	3.2
mm	(F)CPEV telecommunication and telephone lines						
	HP Heat resistant wires for fire and other alarm devices						
	KP/AE Wires of alarm devices in fire dept.						
	IP For intercom						
mm <sup>2</sup>							

3500E-6 : Applicable wires



## Wire Stripper

**3500E-3/-4/-5/-6/-7**

- High-precision blade with true circular cutting edges will not damage core wires.
- Different colors by the grip for instant awareness of holding position, improving working efficiency.
- Thread cutters for small screws and bolts for M3/M4 (3500E-3/-4/-5 only).
- With holes to attach an anti-drop lanyard.
- Cushion grip with AWG, mm, mm<sup>2</sup> conversion table (3500E-3/-4 only).

No.3500E-3



No.3500E-4



No.3500E-5



No.3500E-6

New



No.3500E-7

New



No.3500E-3



No.3500E-4



No.3500E-5



No.3500E-6



No.3500E-7

Applications For wiring work in switchboards and indoor locations

Code No.	Model No.	OAL (mm)	Weight (g)	Color	SPQ (pcs.)	Outer Ctn. (pcs.)	JAN (4907587)
141013	3500E-3	163	107	Red Black	5	30	007223
141014	3500E-4	163	107	Yellow Black	5	30	007230
141017	3500E-5	163	107	Blue Black	5	30	032201
New 141018	3500E-6	163	106	Green Black	5	30	037206
New 141019	3500E-7	163	107	Purple Black	5	30	037213

Package size...220×75×13mm

## Wire Stripper

**3500E-1/-2**

- Lightweight (100g), compact, handy type.
- High-precision blade with true circular cutting edges will not damage core wires.
- Grip with AWG, mm, mm<sup>2</sup> conversion table.

No.3500E-1



No.3500E-2



No.3500E-1



No.3500E-2



Applications For wiring work of electric and telecommunication equipment

Code No.	Model No.	OAL (mm)	Weight (g)	Color	SPQ (pcs.)	Outer Ctn. (pcs.)	JAN (4907587)
141011	3500E-1	155	100	Red	5	30	014108
141012	3500E-2	155	100	Yellow	5	30	014115

Package size...220×75×13mm

### Applicable wire sizes

	AWG	24	22	20	18	16	14	12
3500E-1	Core wire dia. (mm)	0.5	0.65	0.8	1.0	1.3	1.6	2.0
3500E-3	Nominal cross section (mm <sup>2</sup> )	0.2	0.3	0.5	0.8	1.3	2.0	3.3
3500E-2	AWG	30	28	26	24	22	20	18
3500E-4	Core wire dia. (mm)	0.25	0.3	0.4	0.5	0.65	0.8	1.0
	Nominal cross section (mm <sup>2</sup> )	0.05	0.08	0.13	0.2	0.3	0.5	0.8
3500E-5	Core wire dia. (mm)	0.65	0.9	1.0	1.2	1.6	2.0	2.6
	Nominal cross section (mm <sup>2</sup> )	0.3	0.5	0.75	1.25	2.0	3.5	5.5
3500E-6	Core wire dia. (mm)	1.2	1.6	2.0	2.6	3.2		
	Nominal cross section (mm <sup>2</sup> )	1.25	2.0	3.5	5.5	8.0		
3500E-7	Core wire dia. (mm)	0.65	0.9	1.2	1.6	2.0		
	Nominal cross section (mm <sup>2</sup> )	—	—	—	2.0	3.5		

\* Some Teflon wires may not be supported.

## Cautions

- Confirm the appropriate applications, size, and way of use before use.
- Be careful of the electric short circuit and electric shock.
- Wear protective glasses during use.
- Don't keep this product where children can reach.
- If the anti-drop lanyard hole is pulled by excessive force, it may be torn off and there is a risk of dropping of the product.
- Do not use the attachment hole for the anti-drop lanyard in the following cases: when the product received an excessive shock once; when any defect, deformation, or quality change are detected; or when the product is used under extremely high or low temperature.

## VESSEL Co., Inc.

17-25, Fukae-Kita 2-chome, Higashinari-ku, Osaka 537-0001 JAPAN  
Tel: +81(0)6 6976 7778 Fax: +81 (0)6 6972 9441  
URL: www.vessel.co.jp/english E-mail: export@vessel.co.jp

### VESSEL EUROPE

contact@vessel-europe.com  
www.vessel-europe.com

### VESSEL TOOLS U.S.A., INC.

sales@vesseltoolsusa.com  
www.vesseltoolsusa.com

### Distributed by

25032721.02

● Specifications, dimensions, and others may be subject to change without prior notice.